

LEDspan Lay-In Grid Fixture

Model No: **LLIG**



Rigel



Features

- ▶ LEDspan's efficiency leading Lay-in Grid Fixture.
- ▶ Powdercoated epoxy paint finish with IP65 rating for sterile areas.
- ▶ 1mm steel body & 1.2mm steel face frame - removable from room side with 8 no. stainless steel screws.
- ▶ Emergency 3hr battery back-up version available.
- ▶ All Fixings 304 stainless steel.
- ▶ Options - Fully Stainless Steel. Magnetically fixed face frame for screw-less finish.
- ▶ Choice of diffuser available - 90% transmittance/Opal/Prismatic.
- ▶ 31W LED is comparable to 4x14W T5 Fluorescent.
- ▶ 42W LED is comparable to 4x24W T5 Fluorescent.
- ▶ 54W LED is comparable to ;
 - 4x28W T5 Fluorescent.
 - 4x36W T5 Fluorescent.
- ▶ >1% lumen depreciation @ 6,000 hrs.
- ▶ LEDspan underdrive technology for reduced heat and increased lifetime.

Model Options

Power :	31W, 42W, 54W
Voltage:	85V-260Vac
Power Factor:	>0.95
Luminous Flux:	>3,600lm - >6,500lm
LED's:	Everlight
Colour Temperature:	4,000K (+/-200K, 3 step Macadam)
Operating Life:	>50,000 Hours
Beam Angle:	120°
CRI:	>80Ra
Efficiency:	>120lm/W
Product Code LLIG1:	610x610x45mm
Product Code LLIG2:	595x595x45mm

“*Leaders in Energy
Efficient Cleanroom
Lighting Excellence*”



LEDspan operates a continuous improvement policy and reserves the right to change specification at any time.

www.LEDspan.com